

Trademark / Model		Hoval RoofVent® SP			Unit
		6-P	9-P	9-Q	
Type		NRVU, UVU			–
Drive		Variable speed drive			–
Heat recovery system		none			–
Thermal efficiency of heat recovery ($\eta_{t, nrvu}$)		–			%
Nominal flow rate (q_{nom})		1.67	2.5	2.5	m³/s
Effective electric power input (P)		1.2	2.3	2.3	kW
Internal specific fan power (SFP _{int})		162	65	65	W/(m³/s)
Face velocity		3.106	3.273	3.273	m/s
Nominal external pressure ($\Delta p_{s, ext}$)	Supply air	0	0	0	Pa
	Extract air	–	–	–	
Internal pressure drop of ventilation components ($\Delta p_{s, int}$)	Fresh air/supply air	–	–	–	Pa
	Extract air/exhaust air	–	–	–	
Static efficiency of the fans (η_{fan}) in accordance with Regulation (EU) No 327/2011		69.0	63.6	63.6	%
Maximum leakage rate	External	≤ 1	≤ 1	≤ 1	%
	Internal	–	–	–	
Energy classification of the filters (class acc. to ISO 16890, final pressure difference)	Supply air ePM ₁ 55 %	D	D	D	–
	Extract air ePM ₁₀ 65 %	–	–	–	
Visual filter warning		Displayed on the operating unit			–
Casing sound power level (L _{WA})		77	81	81	dB(A)
Disassembly instructions		Devices that are no longer functional must be dismantled by a specialist company and disposed of at suitable collection points.			–
Contact details		Hoval Aktiengesellschaft Austrasse 70, 9490 Vaduz, Liechtenstein www.hoval.com			

Product information according to Commission Regulation (EU) 1253/2014, Article 4(2)